quarelex

Lithium-ion(LiFePO4) E-Bike/E-Trike Power Battery 72V - 50Ah / 100Ah

KEY FEATURES

Nominal Voltage: 76.8V

Capacity: 50Ah, 100Ah, Customizable Dimensions: Standard or Customizable

IP Grade: IP65

Cell Chemistry: Lithium Iron Phosphate (LiFePO4) Monitoring: Bluetooth, LCD Screen(optional) Lifespan: >3500 cycles @80% DoD, 25°C(77°F), 0.5C



Specifications

Model	QM72-50	QM72-100
Electrical		
Nominal Voltage	76.8 V	
Operation Voltage	60 - 87.6 V	
Rated Capacity	50 Ah	100 Ah
Rated Energy	3.84 kWh	7.68 kWh
Estimated Range Per 100% SOC	65-75 miles (105-120 km) @ 50km/h	130-150 miles (210-240 km) @ 50km/h
Suggested DoD	< 90%	
Max DoD	100%	
Self-Discharge	< 3% per Month	
Cells Type	LiFeP04 Prismatic	
Cell Model	3.2 V 50 Ah	3.2 V 100 Ah
Cells Configuration	24S1P	24S1P
Balancing	400 n	nA, Active Balancing
Charge		
Charge Voltage	72 V	
BMS Charge Voltage Cut-Off		72 V
Recommended Charge Current	< 25 A	< 50 A
Max. Continuous Charge Current	50 A	100 A
Charge Temperature	0 - 55 °C (32 - 131 °F)	
Discharge		
Max. Continuous Discharge Current	60 A	100 A
Peak Discharge Current	100 A @ 10S	200 A @ 10S
Recommended Low Voltage Cut-Off	69.6 V	
BMS Discharge Voltage Cut-Off	60 V	
Discharge Temperature	-20 - 60 °C (-4 - 140 °F)	
Mechanical		
Dimensions	460 * 230 * 160 mm (18.11 * 9.06 * 6.3 inch)	640 * 240 * 180 mm (25.2 * 9.45 * 7.09 inch)
Weight	36 kg (79.37 lbs)	63 kg (138.89 lbs)
Terminal Type	Charge: Anderson, Discharge: Anderson	
Case Material	Powder Coated Steel	
Enclosure Protection	IP65	
Communication		
LCD Screen	Yes	Yes
Bluetooth	Yes	Yes
CAN	Yes	Yes
Safety And Warranty		
Protection Function	Overcharge, Over-discharge, Over current, Short Circuit, Over Temperature, Under Temperature	
Storage	0 - 40 °C (32 - 104 °F), < RH 80%, > 60% SOC	
Warranty	2 Years	
Lifespan	10 years or 3500 Cycles @ 25°C, 80% EOL	
Certificates	CE, RoHS, UN38.3, IEC, MSDS	

^{1.} All specifications shown above are subject to change during products improving at any time without prior notice.

^{2.} For other batteries not listed above, customization is also available.